

## SAFETY DATA SHEET

#### Monensin Solution

### Section 1. Identification

GHS product identifier : Monensin Solution
Product code : Not available.
Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Research.

**Area of application**: Industrial applications.

**Supplier/Manufacturer**: BioLegend Inc.

8999 BioLegend Way

San Diego, CA 92121 - USA

Tel: +1-858-455-9588 (7:00AM – 5:00PM PT, M-F)

e-mail address of person responsible for this SDS

: cs@biolegend.com

Emergency telephone number (with hours of

operation)

: +1-858-455-9588 (7:00AM – 5:00PM PT, M-F)

### Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

(Narcotic effects) - Category 3

**GHS label elements** 

Hazard pictograms :





Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapor.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 1/13

Monensin Solution

### Section 2. Hazards identification

Prevention: P280 - Wear protective gloves, protective clothing and eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P271 - Use only outdoors or in a well-ventilated area.

P261 - Avoid breathing vapor.

P264 - Wash thoroughly after handling.

Response : P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for

breathing. Call a POISON CENTER or doctor if you feel unwell.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Hazards not otherwise

: Prolonged or repeated contact may dry skin and cause irritation.

### classified

# Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Not available.

: Mixture

Ingredient name	Other names	%	CAS number
<b>e</b> thanol	ethyl alcohol	≥50 - ≤75	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 2/13

### Section 4. First aid measures

#### Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation**: Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

**Ingestion**: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 3/13

### Section 4. First aid measures

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 4/13

### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
ethanol	ACGIH TLV (United States, 1/2023).  STEL: 1000 ppm 15 minutes.  NIOSH REL (United States, 10/2020).  TWA: 1000 ppm 10 hours.  TWA: 1900 mg/m³ 10 hours.  OSHA PEL (United States, 5/2018).  TWA: 1000 ppm 8 hours.  TWA: 1900 mg/m³ 8 hours.

#### Biological exposure indices

None known.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 5/13

### Section 8. Exposure controls/personal protection

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.

Color : Cear. Colorless.

Odor : Not available.

Odor threshold : Not available.

pH : Not available.

Melting point/freezing point : Not available.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 6/13

### Section 9. Physical and chemical properties

**Boiling point, initial boiling** point, and boiling range

: 92.222°C (198°F)

Flash point

Closed cup: 23.889°C (75°F)

**Flammability** Lower and upper explosion limit/flammability limit

: Not available. : Not available.

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
<b>e</b> thanol	42.94865	5.7				

**Relative vapor density** 

Not available. Not available.

Relative density **Density** 

Not available.

Solubility(ies)

Media Result cold water Soluble Soluble hot water

Partition coefficient: noctanol/water

Not applicable.

**Auto-ignition temperature** 

Ingredient name °C °F Method **ethanol** 455 851 DIN 51794

**Decomposition temperature** 

: Not available. Not available.

**Viscosity** 

**SADT** 

: Not available.

**Particle characteristics** 

Median particle size

: Not applicable.

**Other information** 

Physical/chemical properties comments : No additional information.

### Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** 

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials** 

: Reactive or incompatible with the following materials: oxidizing materials

Date of issue/Date of revision

: 11/29/2023 Date of previous issue : 11/08/2017

Version : 2

7/13

### Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
<b>e</b> thanol	LC50 Inhalation Dusts and mists LC50 Inhalation Vapor LD50 Oral		124700 mg/m³ >61 mg/l 7 g/kg	4 hours 4 hours -

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<b>e</b> thanol	Eyes - Severe irritant	Rabbit	-	500 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Conclusion/Summary

: Not available.

Carcinogenicity

**Conclusion/Summary** 

: Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
<b>e</b> thanol	-	1	-

#### Reproductive toxicity

**Conclusion/Summary** 

: Not available.

**Teratogenicity** 

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
<b>e</b> thanol	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 8/13

### **Section 11. Toxicological information**

ingestion : Can cause central nervous system (CNS) depression.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

····ca

: Not available.

**Potential delayed effects** 

: Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Carcinogenicity
 Mo known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Reproductive toxicity
 Mo known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

	(	(mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
<b>e</b> thanol	7000	N/A	N/A	N/A	124.7

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 9/13

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
<b>e</b> thanol	Acute EC50 17.921 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 25500 μg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 μg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - <i>Gambusia holbrooki</i> - Larvae	12 weeks

**Conclusion/Summary** 

: Not available.

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
<b>e</b> thanol	-0.35	-	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 10/13

### **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	UN1170	UN1170	UN1170
UN proper shipping name	Ethanol solutions	ETHANOL SOLUTION	Ethanol solution
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	No.	No.	No.

**Additional information** 

**DOT Classification** : Limited quantity Yes.

> Packaging instruction Exceptions: 4b, 150. Non-bulk: 203. Bulk: 242. Quantity limitation Passenger aircraft/rail: 60 L. Cargo aircraft: 220 L.

Special provisions 24, B1, IB3, T2, TP1

**IMDG** : Emergency schedules F-E, S-D

Special provisions 144, 223

**IATA Quantity limitation** Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355.

Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger

Aircraft: 10 L. Packaging instructions: Y344.

Special provisions A3, A58, A180

Special precautions for user Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according

to IMO instruments

: Not available.

### Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

**Class I Substances** 

: Not listed

**Clean Air Act Section 602** 

Class II Substances

: Not listed

**DEA List I Chemicals** (Precursor Chemicals) : Not listed

**DEA List II Chemicals** (Essential Chemicals) Not listed

**SARA 302/304** 

Date of issue/Date of revision Version : 2 : 11/29/2023 Date of previous issue : 11/08/2017 11/13

### Section 15. Regulatory information

#### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : FLAMMABLE LIQUIDS - Category 3

EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

HNOC - Defatting irritant

#### **Composition/information on ingredients**

Name	%	Classification
<b>e</b> thanol	≥50 - ≤75	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 HNOC - Defatting irritant

#### **SARA 313**

Not applicable.

**State regulations** 

Massachusetts : The following components are listed: ETHYL ALCOHOL

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL

Pennsylvania : The following components are listed: ETHANOL

California Prop. 65

his product does not require a Safe Harbor warning under California Prop. 65.

#### **International regulations**

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

### Section 16. Other information

#### National Fire Protection Association (U.S.A.)



Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 12/13

### Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
AMMABLE LIQUIDS - Category 3	On basis of test data
EYE IRRITATION - Category 2A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	

**History** 

Date of issue/Date of

revision

: 11/29/2023

Date of previous issue

: 11/08/2017

Version

: 2

Prepared by

: Sphera Solutions

Key to abbreviations

: ATE = Acute Toxicity Estimate

AMP = Acceptable maximum peak above the acceptable ceiling concentration for an

8-hr shift

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

References

: HCS (U.S.A.) - Hazard Communication Standard

International transport regulations

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 11/29/2023 Date of previous issue : 11/08/2017 Version : 2 13/13